

## Echipament tubulatura ON/OF



### ARY18U

● 5.40kW / 18,400BTU/h  
● 6.00kW / 20,500BTU/h

- Compacte, ultra subtiri (217mm) ,cu un design care economiseste spatiu
- Eficienta ridicata a climatizarii spatiilor cu ajutorul tubulaturii flexibile si grilelor de refulare
- Posibilitate de aport aer proaspat la unitatea interioara
- Programare functionare saptamanala cu ajutorul telecomenzii de perete cu fir
- Control precis si confortabil prin instalarea unui senzor de caldura in telecomanda ,iar prin selectarea functiei de comutare utilizatorul poate selecta pozitia senzorului.

Date tehnice:

Model	Unitate interioara		<b>ARY18U</b>
	Unitate exterioara		<b>AOY18U</b>
Clasa energetica (incalzire/racire)			C/C
Capacitate	Racire	kw	5,4
	Incalzire		6,0
	Racire	BTU/h	18400
	Incalzire		20500
Eliminarea umiditatii		l/h	1,6
Nivel de zgomot (interior)	Racire/H/M/L		43/40/36
Nivel de zgomot (exterior)	Racire	dB(A)	52
Ventilare	Interior	m3/h	1000
	Exterior		3200
Tensiune de alimentare		V/Ø/Hz	230/1/50
Curent alimentare	Racire	A	8,8
	Incalzire		8,7
Putere consumata	Racire	kw	1,92
	Incalzire		1,87
EER	Racire	W/W	2,81
COP	Incalzire		3,21
Dimensiuni HxWxD	Interior	mm	217x953x595
		kg(lbs)	25(55)
	Exterior	mm	650x830x320
		kg(lbs)	52(115)
Dimensiune teva (micaØ mareØ)		mm	6,35/15,88
Lungime teava max/Diferenta de nivel		m	20/8
Intervalul permis al temperaturii exterioare	Racire	°C	0..+43
	Incalzire		-6..+24
Refrigerant			R410A