

## Echipament tubulatura ON/OF



**ARY7U**  
C 2.15kW / 7,300BTU/h  
H 2.45kW / 8,400BTU/h

- Compacte, ultra subtiri (217mm) ,cu un design care economiseste spatiu
- Eficienta ridicata a climatizarii spatiilor cu ajutorul tubulaturii flexibile si grilelor de refulare
- Posibilitate de aport aer proaspat la unitatea interioara
- Programare functionare saptamanala cu ajutorul telecomenzii de perete cu fir
- Control precis si confortabil prin instalarea unui senzor de caldura in telecomanda ,iar prin selectarea functiei de comutare utilizatorul poate selecta pozitia senzorului.

Date tehnice:

Model	Unitate interioara		<b>ARY7U</b>
	Unitate exterioara		<b>AOY7U</b>
Clasa energetica (incalzire/racire)			C/C
Capacitate	Racire	kw	2,15
	Incalzire		2,45
	Racire	BTU/h	7300
	Incalzire		8400
Eliminarea umiditatii		l/h	0,8
Nivel de zgomot (interior)	Racire/H/M/L		31/28/26
Nivel de zgomot (exterior)	Racire	dB(A)	48
Ventilare	Interior	m3/h	340
	Exterior		1600
Tensiune de alimentare		V/Ø/Hz	230/1/50
Curent alimentare	Racire	A	3,6
	Incalzire		3,6
Putere consumata	Racire	kw	0,76
	Incalzire		0,76
EER	Racire	W/W	2,83
COP	Incalzire		3,22
Dimensiuni HxWxD	Interior	mm	217x663x595
		kg(lbs)	18(40)
	Exterior	mm	530x750x250
		kg(lbs)	28(62)
Dimensiune teva (micaØ mareØ)		mm	6,35/9,52
Lungime teava max/Diferenta de nivel		m	15/8
Intervalul permis al temperaturii exterioare	Racire	°C	0..+43
	Incalzire		-6..+24
Refrigerant			R410A