

## Echipament tubulatura ON/OF



**ARY9U**  
C 2.70kW / 9,200BTU/h  
H 3.10kW / 10,600BTU/h

- Compacte, ultra subtiri (217mm) ,cu un design care economiseste spatiu
- Eficienta ridicata a climatizarii spatiilor cu ajutorul tubulaturii flexibile si grilelor de refulare
- Posibilitate de aport aer proaspat la unitatea interioara
- Programare functionare saptamanala cu ajutorul telecomenzii de perete cu fir
- Control precis si confortabil prin instalarea unui senzor de caldura in telecomanda ,iar prin selectarea functiei de comutare utilizatorul poate selecta pozitia senzorului.

Date tehnice:

Model	Unitate interioara		<b>ARY9U</b>
	Unitate exterioara		<b>AOY9U</b>
Clasa energetica	(incalzire/racire)		C/C
Capacitate	Racire	kw	2,7
	Incalzire		3,1
	Racire	BTU/h	9200
	Incalzire		10600
Eliminarea umiditatii		l/h	1
Nivel de zgomot (interior)	Racire/H/M/L	dB(A)	35/33/31
Nivel de zgomot (exterior)	Racire		48
Ventilare	Interior	m3/h	420
	Exterior		1600
Tensiune de alimentare		V/Ø/Hz	230/1/50
Curent alimentare	Racire	A	4,4
	Incalzire		4,5
Putere consumata	Racire	kw	0,96
	Incalzire		0,96
EER	Racire	W/W	2,81
COP	Incalzire		3,23
Dimensiuni HxWxD	Interior	mm	217x663x595
		kg(lbs)	18(40)
	Exterior	mm	530x750x250
		kg(lbs)	30(66)
Dimensiune teva (micaØ mareØ)		mm	6,35/9,52
Lungime teava max/Diferenta de nivel		m	15/8
Intervalul permis al temperaturii exterioare	Racire	°C	0..+43
	Incalzire		-6..+24
Refrigerant			R410A